



**KYORENE®**  
THE GRAPHENE FIBER

# 00 - 111

## SPECIFICATION SHEET

GENERAL  
PURPOSE

Global Recycled  
Standard



EN388



4121A

EN407



X1XXXX



CUT



### ATTRIBUTES:

- 18 gauge grey Kyorene® graphene recycled polyester liner
- Black HCT® nano-foam nitrile palm coating

### FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Picking, fastening components
- Assembling and mounting components
- Fastening components, parts
- General handling
- Transport & Logistic

### CATEGORY:

- Kyorene®

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



Oeko-Tex®  
Standard 100



TOUCH  
SCREEN

### PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

### PERFORMANCE LEVEL:

EN388: 4121A

ABRASION		1	2	3	4	
CUT		1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F



VERIFIED GRAPHENE  
PRODUCER  
THE GRAPHENE COUNCIL



Hybrid Coating Technology