



**KYORENE®**  
THE GRAPHENE FIBER

# 01 - 103

## SPECIFICATION SHEET

GENERAL  
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



Oeko-Tex®  
Standard 100



TOUCH  
SCREEN

### ATTRIBUTES:

- 18 gauge grey Kyorene® graphene liner
- Black HCT® micro-foam nitrile palm coating

### FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh

### APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Maintenance
- Warehousing
- Landscaping

### CATEGORY:

- Kyorene®

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



VERIFIED GRAPHENE®  
PRODUCER  
THE GRAPHENE COUNCIL



Hybrid Coating Technology

### PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

### PERFORMANCE LEVEL:

EN388: 4121A

ABRASION		1	2	3	4	5
CUT		1	2	3	4	5
TEAR		1	2	3	4	5
PUNCTURE		1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F