



EN388



4X42C



CUT



Oeko-Tex[®]
Standard 100



ATTRIBUTES:

- 18 gauge grey Kyorene[®] Pro graphene liner
- Black HCT[®] micro foam nitrile palm coating

FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Automotive manufacturing
- Appliance manufacturing
- Metal stamping
- Sheet metal handling
- Handling extruded plastics
- Construction

CATEGORY:

- Kyorene[®] Pro

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



VERIFIED GRAPHENE[®]
PRODUCER
THE GRAPHENE COUNCIL



Hybrid Coating Technology

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X42C

ABRASION		1	2	3	4	5
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	5
PUNCTURE		1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F