



KYORENE®
THE GRAPHENE FIBER

09 - 605R1

SPECIFICATION SHEET



EN388



4X42F

EN407



X1XXXX



CUT

ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Black Crinkle Latex palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Bottling
- Glass handling
- Heavy material handling

CATEGORY:

- Kyorene®

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



Oeko-Tex®
Standard 100



PACKAGING:

| GLOVE SIZE | 6 | 7 | 8 | 9 | 10 | 11 |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE | 72 | 72 | 72 | 72 | 72 | 72 |

PERFORMANCE LEVEL:

EN388: 4X42F

| ABRASION | | 1 | 2 | 3 | 4 | 5 |
|--------------|---|---|---|---|---|---|
| CUT | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE | | 1 | 2 | 3 | 4 | 5 |
| CUT TDM TEST | A | B | C | D | E | F |



VERIFIED GRAPHENE®
PRODUCER
THE GRAPHENE COUNCIL



Hybrid Coating Technology