


 Oeko-Tex®  
 Standard 100

**ATTRIBUTES:**

18G graphene liner with acrylic lining, black microfoam nitrile palm coating with transparent TPU membrane, reinforced thumb crotch area, hook-and-loop (Velcro) closure.

**FEATURES:**

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

**APPLICATIONS:**

- Port and container companies, offshore, scaffolding construction, heavy petrochemical industry, construction and civil engineering, shipyards, wind turbine technicians.

**CATEGORY:**

- **Kyorene® Pro**

**CARE INSTRUCTIONS:**

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

**TECHNOLOGIES:**
**PACKAGING:**

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	24					

**PERFORMANCE LEVEL:**
**EN388: 4X32EP**

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT	F			P		

