



EN388



4X42C

EN16350



CUT


 Oeko-Tex®
 Standard 100


ATTRIBUTES:

- 18 gauge grey Kyorene® Pro graphene ESD liner
- Black HCT® nano-foam nitrile knuckle coating

FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Delivery of parts to production line
- Loading and unloading rough parts or boxes
- Picking parts and accessories
- Assembly of sharp parts
- Handling sharp metal parts
- Light duty stamping
- Maintenance

CATEGORY:

- **Kyorene® Pro**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGIES:



PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X42C

ABRASION		1	2	3	4	5
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	5
PUNCTURE		1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F

