



EN16350



EN388



4X42F


 Oeko-Tex®
 Standard 100

PACKAGING:

| | | | | | | |
|------------|--------|-----|--------|-------|-------|------|
| GLOVE SIZE | 5/6 | 7 | 8 | 9 | 10 | 11 |
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE | 72 | | | | | |

PERFORMANCE LEVEL:

EN388: 4X42F

| | | | | | | |
|--------------|---|---|---|---|---|---|
| ABRASION | | 1 | 2 | 3 | 4 | |
| CUT | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | | 1 | 2 | 3 | 4 | |
| PUNCTURE | | 1 | 2 | 3 | 4 | |
| CUT TDM TEST | A | B | C | D | E | F |
| IMPACT | F | | | P | | |


VERIFIED GRAPHENE®
 PRODUCER
 THE GRAPHENE COUNCIL

ATTRIBUTES:

- 18 gauge grey Kyorene® Pro graphene liner
- Black HCT® nanofoam nitrile palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free
- No stainless steel or fiberglass
- Ergonomically shaped for superior fit

APPLICATIONS:

- Final assembly
- Machining
- Equipment maintenance and repair

CATEGORY:

- KYORENE PRO

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGY:
