



EN511



X2X

EN407



X2XXXX

EN388



4X43FP



CUT


 Oeko-Tex®  
 Standard 100


### ATTRIBUTES:

- 18 gauge grey Kyorene® Pro graphene liner & 7g poly-acrylic lining
- Black HCT® microfoam nitrile palm coating

### FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Maintenance refineries and ports
- Transport logistics
- Heavy parts handling
- Construction
- Off-shore drilling

### CATEGORY:

- **Kyorene® Pro**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

### TECHNOLOGIES:



### PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	24	24	24	24	24	24

### PERFORMANCE LEVEL:

EN388: 4X43FP

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT	F			P		