

GENERAL
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



TOUCH
SCREEN



Oeko-Tex®
Standard 100



THERMAL
REGULATION

ATTRIBUTES:

- 15 gauge grey Kyorene® graphene liner
- HCT® micro foam nitrile coating with dotted palm

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Automotive manufacturing
- Light manufacturing
- Maintenance
- Warehousing
- Landscaping

CATEGORY:

- **Kyorene®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGIES:

PACKAGING:

GLOVE SIZE	7	8	9	10	11
CUFF COLOR	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4121A

ABRASION		1	2	3	4	
CUT		1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F

