



EN388



4X42D



CUT


**TOUCH
SCREEN**

 Oeko-Tex®
 Standard 100

 THERMAL
 REGULATION

ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Black HCT® micro foam nitrile palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Automotive manufacturing
- Appliance manufacturing
- Metal stamping
- Sheet metal handling
- Construction
- Extruded plastics

CATEGORY:

- **Kyorene®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGIES:

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X42D

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F