



EN388



4X41D


 ANSI
A4
 CUT

 Oeko-Tex®
 Standard 100


PACKAGING:

GLOVE SIZE	5/6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72					

PERFORMANCE LEVEL:

EN388: 4X41D

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT	F			P		


VERIFIED GRAPHENE®
 PRODUCER
 THE GRAPHENE COUNCIL

ATTRIBUTES:

- 24G graphene nylon liner
- Black nitrile HCT Lite palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free
- No stainless steel or fiberglass
- Ergonomically shaped for superior fit

APPLICATIONS:

- Maintenance data center
- Appliance manufacturing
- Steel processing
- Automotive manufacturing

CATEGORY:

- KYORENE PRO MAX

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGY:

