



EN388



2X4XD



CUT


 Oeko-Tex[®]
 Standard 100


ATTRIBUTES:

- Harm protection with high cut resistance level D
- For all-round work with hand attachment for better fit and easy doing with gloves

FEATURES:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh

APPLICATIONS:

- Automotive
- Glass industry
- Metal fabrication
- White goods
- Machinery equipment

CATEGORY:

- **Kyorene[®] Pro**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

PACKAGING:

SLEEVE SIZE	S, M, L, XL
PER CASE	144

PERFORMANCE LEVEL:

EN388: 2X4XD

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE	X	1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F

