


**EN388**

**3X42D**

**CUT**

 Oeko-Tex®  
 Standard 100


### PACKAGING:

GLOVE SIZE	5/6	7	8	9	10	11
CUFF COLOR						
PER CASE	72					

### PERFORMANCE LEVEL:

**EN388: 3X42D**

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT	F			P		


**VERIFIED GRAPHENE®**  
 PRODUCER  
 THE GRAPHENE COUNCIL

### ATTRIBUTES:

- 24G Gray graphene nylon and spandex liner with black Soft PU palm coating, reinforcement between thumb and index finger.

### FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- No stainless steel or fiberglass
- Ergonomically shaped for superior fit

### APPLICATIONS:

- Automotive manufacturing
- Sheet metal handling
- Handling extruded plastics
- Fine assembly

### CATEGORY:

- KYORENE PRO MAX

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.