


EN388

4X32F

CUT

Oeko-Tex®
Standard 100


PACKAGING:

GLOVE SIZE	5/6	7	8	9	10	11
CUFF COLOR						
PER CASE	72					

PERFORMANCE LEVEL:

EN388: 4X32F

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT	F			P		

ATTRIBUTES:

- 18g Gray Kyorene® Pro Graphene A6 Liner
- Black Polyurethane Palm Coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- No stainless steel or fiberglass
- Ergonomically shaped for superior fit

APPLICATIONS:

- Metal fabrication
- Steel processing
- Automotive manufacturing
- Construction

CATEGORY:

- KYORENE PRO

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

TECHNOLOGY:

